

## RefLED ES50 V2

RefLED ES50 V2 5W 345LM 840 36° SL

**0026580**



### Range Features

- Up to 90% energy saving comparing to halogen.
- High light output - real retrofit for the halogen lamps
- Perfect shape and size for a perfect fit in your luminaire.
- Choice of beam angles to suit lighting needs (36 degree or ultra wide beam).
- Available in different colour temperatures: 3000K Warm white, 4000K Cool white. and 6500K Daylight.
- Dimmable option available on approved dimmers\*.
- Highly efficient - up to 71Lm/W.
- Average rated life of 15,000 hours.
- 3 Year Warranty.



### PRODUCT OVERVIEW

Beam angle(°)	36
Lamp finish	White
Lamp shape	GU10/ES63
Colour temperature (K)	4000
CRI (Ra)	80
Dimmable	No
EAN code	5410288265803
Energy class	A+
Equivalent watt (W)	50
Cap/Base	GU10
Beam angle(°)	36
Type	RefLED ES50 V2
Watt (Nominal) (W)	5
Light colour	840 Cool White
Ordering number	0026580
Efficacy (Rated) (lm/w)	69
Average life (Rated) (h)	15000
Luminous flux (Rated) (lm)	345
Technology	LED
Voltage (V)	220-240
Colour consistency (SDCM)	6

### DATA TABLE

#### General data

Average life (Nominal) (h)	15000
Control gear required	No

## RefLED ES50 V2

RefLED ES50 V2 5W 345LM 840 36° SL

**0026580**

<b>Lamp finish</b>	White
<b>Lamp shape</b>	GU10/ES63
<b>Control gear availability</b>	No
<b>Dimmable</b>	No
<b>EAN code</b>	5410288265803
<b>Energy class</b>	A+
<b>Energy saving lamp</b>	Yes
<b>General application</b>	Retail; Hospitality; Museums; Residential & Consumer
<b>Intended purpose</b>	General lighting
<b>Cap/Base</b>	GU10
<b>Type</b>	RefLED ES50 V2
<b>No. of switching cycles before premature failure (min)</b>	>20000
<b>Optimal operating condition (°C)</b>	25
<b>Ordering number</b>	0026580
<b>Range features</b>	<p>Up to 90% energy saving comparing to halogen.                      High light output - real retrofit for the halogen lamps                      Perfect shape and size for a perfect fit in your luminaire.                      Choice of beam angles to suit lighting needs (36 degree or ultra wide beam).                      Available in different colour temperatures: 3000K Warm white, 4000K Cool white. and 6500K Daylight.                      Dimmable option available on approved dimmers*.                      Highly efficient - up to 71Lm/W.                      Average rated life of 15,000 hours.                      3 Year Warranty.</p>
<b>Product name</b>	RefLED ES50 V2 5W 345LM 840 36° SL
<b>Average life (Rated) (h)</b>	15000
<b>Special purpose lamp</b>	No
<b>Starting time (max) (s)</b>	<0,5
<b>Technology</b>	LED
<b>Sales pack quantity</b>	6
<b>Warm-up time to 60% of full light (max) (s)</b>	< 1s => 60%
<b>E-number FI</b>	4740253
<b>Product features</b>	<p>Good every day quality from a brand you can trust. RefLED ES50 V2 delivers a cost effective solution to replacing halogen GU10 with LED offering 345lm of light equivalent to a 50W halogen lamp while extending lamp life to 15,000 hours. GU10 cap. 36 degree beam angle in Cool white 4000K. Backed by a 3 year warranty.</p>
<b>Optical data</b>	
<b>Beam angle(°)</b>	36
<b>Colour temperature (K)</b>	4000
<b>CRI (Ra)</b>	80

## RefLED ES50 V2

RefLED ES50 V2 5W 345LM 840 36° SL

**0026580**

<b>Beam angle(°)</b>	36
<b>Light colour</b>	840 Cool White
<b>Lumen maintenance at end of nominal life (%)</b>	85
<b>Luminous flux (Nominal) (lm)</b>	345
<b>Peak intensity (cd)</b>	1000
<b>Luminous flux (Rated) (lm)</b>	345
<b>Suitable for accent lighting</b>	Yes
<b>Colour Consistency</b>	6
<b>Beam angle (Rated) (°)</b>	36
<b>Adjustable chromaticity</b>	No
<b>Colour consistency (SDCM)</b>	6

### Electrical data

<b>Current (A)</b>	25
<b>Drive current (mA)</b>	25
<b>Equivalent watt (W)</b>	50
<b>kWh per 1000 hours burning time</b>	5
<b>Lamp power factor</b>	0.8
<b>Watt (Nominal) (W)</b>	5
<b>Efficacy (Rated) (lm/w)</b>	69
<b>Watt (Rated) (W)</b>	5
<b>Voltage (V)</b>	220-240

### Physical data

<b>Max. Lamp Diameter (mm) - D</b>	50
<b>Lamp Length (mm) - C/L</b>	54
<b>Single packaging type</b>	Box/Sleeve
<b>Weight (kg)</b>	0.04
<b>Lamp dimension equal to filament lamp equivalent</b>	Yes
<b>Designed for optimum use in non standard conditions</b>	No
<b>Fluorescent lamp replacement</b>	No
<b>Inner package net weight (kg)</b>	0.25
<b>Inner package dimensions (L x W x H) (cm)</b>	16.70 x 11.30 x 9.70
<b>Outer package dimensions (L x W x H) (cm)</b>	60.80 x 18.10 x 23.00
<b>Single package dimensions (L x W x H) (cm)</b>	6.70 x 5.10 x 5.10

## RefLED ES50 V2

RefLED ES50 V2 5W 345LM 840 36° SL

**0026580**

