


128, av. du Maréchal-de-Lattre-de-Tassigny - 87045 LIMOGES Cedex Tel.: +33(0)5 55 06 87 87 - Fax: +33(0)5 55 06 88 88 www.legrand.com

TV multi-outlet adapter with SPD German Standard



1. USE

Attractive case for integrated connections.

For connecting and protecting all appliances around the TV set.

Can hide and manage cables.


For integration in a TV cabinet (non-slip feet) or can be fixed to the wall with screws (not provided).


Equipped with an SPD


Supplied with self-locking cable tie to hold the cords together.

2. RANGE


Presentation	Black/Grey
Comprises:	
• 3 x 2P+E sockets - 1 2P+E flush socket - 4 x 2P	
with safety shutter.	6 945 15
• 2 m power supply cord (3 G 1.5 mm ²) with moulded	6 945 95
French-German plug.	6 945 96
 ON/OFF illuminated switch (blue LED). 	
 SPD with illuminated indicator (green LED). 	







210 232 56	Α	В	с
210 252 50	210	232	56



D	E	F
157	117	58.5

5. TECHNICAL CHARACTERISTICS

5.1 Mechanical characteristics

Impact tests: IK 04 Protection against solid/bodies and liquids: IP 20

5.2 Material characteristics

Case: Black painted aluminium + dark grey PP Non-slip feet: Plastic

Halogen-free

UV-resistant

Self-extinguishing: 750°C/30 s for insulating components holding live parts in place. 650°C/30 s for other insulating components.

5.3 Electrical characteristics

Voltage: 230 V~

Power: 3680 W MAX.

- 2P+E sockets: 16 A • 2P sockets: 6 A (6 945 95)
 - 10 A (6 945 96)
 - 2.5 A (6 945 15)

• SPD: Uc: 275 V - 50 Hz

Uoc: 4 kV Isccr: 3.0 kA Up: 1 kV Type: 3

SPD:

• The switch is set to ON and the green LED is lit: The SPD is active and protects any plugged-in appliances.

• The switch is set to ON and the green LED is off: the SPD has protected against lightning but is no longer protecting the plugged-in appliances. Note: The multi-outlet adapter still works but is not protected.

■ 5.4 Climate characteristics

Usage temperature: -5°C to +35°C Storage temperature: -20°C to +70°C

6. CARE

Surface cleaning with a cloth.

Do not use: acetone, tar remover, trichloroethylene.

Caution: Always test before using other special cleaning products.

7. STANDARDS AND APPROVALS

Compliant with installation and manufacturing standards See e. catalogue.