



Watertight enclosure for emergency systems, equipped with illuminated push-button and 2 contacts 1NO+1NC that can be expanded up to 4 contacts. The enclosure has the pre-arrangement for use of green led to indicate the good condition of emergency circuit. It is pre-arranged with a short or long push-button for deliberate operation, or with an intrinsic safety function. Thanks to the emergency hammer, available as an accessory, sealable mask and halogen free materials are ideally suited for applications in areas open to public.

Corrente nominal (A)	125	Classe isolamento	II
Cor	Vermelho RAL 3000	Dim. externas BxHxP (mm)	120x120x50
Grau de protecção	IP55	Instalação	Parede
Material	Tecnopolímero	Resistên. golpes	IK08
Tensão nominal	400	Acessórios	Botão de pressão e 2 contactos
Glow Wire Test	650 °C	Temperatura de instalação	-25 +60 °C
Tipo de material	Livre halogéneos segundo EN 60754-2	Código Electrocod	0321
Nº de contactos instaláveis	4	Termopressão com esfera	70 °C
Norma	EN 60670-1, IEC60670-24	Tensão de isolamento	750 V



DIMENSIONAL

TECHNICAL SYMBOLOGY



II

IP

IP55

IK

IK08

GWT

650 °C



-25 +60 °C



Livre halogéneos
segundo EN 60754-2



70 °C

STANDARDS/APPROVALS

